

IN THE CLAIMS

Please amend the claims as follows.

1. (Previously Presented) A method for operating a conditional access system for broadcast applications, said conditional access system comprising a number of subscribers, each subscriber having a terminal including a conditional access module and a secure device to store entitlements, wherein a source signal is encrypted using a first key (C_W), said first key (C_W) being changed at a rate, said encrypted source signal being broadcasted for receipt by the terminals, wherein entitlement control messages (ECM's) are sent to the secure devices, said ECM's comprising the first keys (C_W) encrypted using a service key (P_T), wherein entitlement management messages (EMM's) are sent to the secure device providing the service key (P_T) required to decrypt encrypted first keys (C_W), wherein a cracked secure device which is used in an unauthorized manner is traced by sending different keys required to obtain the first keys to different terminals or groups of terminals and monitoring the key information provided by a pirate, wherein search EMM's are sent to at least a part of the terminals, said search EMM's providing at least the service key (P_T) and a dummy key (P_{D1} or P_{D2}), at least the search EMM's comprising identifiers identifying the keys (P_T and P_{D1} or P_{D2}), wherein first search EMM's with the keys (P_T and P_{D1}) are sent to a first part of the terminals and second search EMM's with the keys (P_T and P_{D2}) are sent to a second part of the terminals, wherein an ECM identifying the service key (P_T) to be used to decrypt the encrypted first key (C_W), is sent to all secure devices just before the first key (C_W) is needed to decrypt the source signal.

2. (Previously Presented) A method according to claim 1, wherein the encrypted source signal comprises a stream of data packets, wherein successive groups including at least one data packet, are encrypted using successive first key (C_{W1} , C_{W2}, \dots , C_{Wi}, \dots, C_{Wn}), each data packet having a flag indicating the first key (C_{Wi}) to be used for decrypting the data packet, wherein instead of an ECM identifying the service key (P_T) an ECM identifying a dummy key (P_{D1} or P_{D2}) to be used to decrypt a next encrypted first key (C_{Wi}), is sent to the secure devices of the first and second parts of the terminals, respectively, just before the first key (C_{Wi}) is needed to decrypt the source signal, whereas the data packet is encrypted using the previous first key (C_{Wi-1}).
3. (Previously Presented) A method according to claim 1, wherein a set of search EMM's is sent to the terminals, each search EMM providing two keys (P_T and P_{D1} , P_T and P_{D2}, \dots , P_T and P_{Dn}).
4. (Currently Amended) A method for operating a conditional access system for broadcast applications, said conditional access system comprising a number of subscribers, each subscriber having a terminal including a conditional access module and a secure device to store entitlements, wherein a source signal is encrypted using a first key (C_W), said first key (C_W) being changed at a rate, said encrypted source signal being broadcasted for receipt by the terminals, wherein entitlement control messages (ECMs) are sent to the secure devices, said ECMs comprising the first keys (C_W) encrypted using a service key (P_T), wherein entitlement management messages (EMMs) are sent to the secure device providing the service key (P_T) required to decrypt encrypted first keys (C_W), wherein a cracked secure device which is used in an unauthorized manner is traced by sending different keys ~~required to obtain the first keys to~~ different terminals or groups of terminals and monitoring the key information provided by a pirate, wherein a set of search EMMs is sent to at least a part of the terminals, each search EMM of the set comprising a different dummy key (P_D), each of the dummy keys (P_D) being a key other than a correct service key (P_T) for decrypting an encrypted first key (C_W), and each search EMM being sent to a different part of the terminals or group of terminals.

5. (Previously Presented) A method according to claim 3, wherein the terminals are divided into groups, wherein in a first search step the number of search EMM's of the set of search EMM's corresponds to the number of groups.
6. (Currently Amended) A method for operating a conditional access system for broadcast applications, said conditional access system comprising a number of subscribers, each subscriber having a terminal including a conditional access module and a secure device to store entitlements, wherein a source signal is encrypted using a first key (C_W), said first key (C_W) being changed at a rate, said encrypted source signal being broadcasted for receipt by the terminals, wherein entitlement control messages (ECMs) are sent to the secure device, said ECMs comprising the first keys (C_W) encrypted using a service key (P_T), wherein entitlement management messages (EMMs) are sent to the secure devices providing the service key (P_T) required to decrypt encrypted first keys (C_W), wherein a cracked secure device which is used in an unauthorized manner is traced by sending different keys required to obtain the first keys to different terminals or groups of terminals and monitoring the key information provided by a pirate, wherein the source signal or the ECMs are encrypted using a multiple-key or secret-sharing cryptographic algorithm having a plurality of different decrypting keys or shares ($C_i; P_i$) of which any one or any one or more, respectively, is required for decrypting the encrypted source signal or ECMs, respectively, wherein said plurality of different decrypting keys or shares ($C_i; P_i$) are sent to at least a part of the terminals such that different terminals or groups of terminals receive different keys or shares ($C_i; P_i$) according to a predetermined distribution.
7. (Previously Presented) A method according to claim 1, wherein the distribution of the terminals in groups of terminals is varied to trace the cracked secure device.
8. (Previously Presented) A method according to claim 4, wherein the distribution of the terminals in groups of terminals is varied to trace the cracked secure device.

9. (Previously Presented) A method according to claim 6, wherein the distribution of the terminals in groups of terminals is varied to trace the cracked secure device.